

<i>Typ av Dokument</i> Dokument	<i>Sida</i> 1 (30)
<i>Datum</i> 2026-01-14	<i>Dokument-ID</i> DOCID-1165896853-423
<i>Sekretessklass</i> Publik	<i>Version</i> 18.0
<i>Dokumentägare</i> Pålbros, Jonas	<i>Företag</i> Sydkraft Thermal Power AB
<i>Titel</i> STP - HSE-krav entreprenörer	<i>Godkänd av</i> Thunell, Anna

HSE-krav Entreprenörer

For English version see below

Sydkraft Thermal Powers (hädanefter STP) övergripande mål är att ingen skall utsättas för allvarig olycka eller drabbas av arbetsrelaterade sjukdomar.

Detta mål gäller STP:s egen personal och de entreprenörer som arbetar åt STP.

För att nå detta krävs att samtliga samarbetar för en säker arbetsmiljö, både egen personal och samtliga entreprenörer.

Alla nedan nämnda krav på entreprenörer och leverantörer skall ingå i det pris som överenskommes mellan parterna.

Datum **Ändring**

2019-11-08 Mindre ändringar

2021-09-16 Mindre ändringar

2022-03-08 Mindre ändringar

2022-07-11 Uppdateringar gällande kniv med öppet blad

2024-03-15 Förtydligande och mindre ändringar kapitel 11. Arbete på höjd.

2024-06-26 Uppdatering av EN-standard för flamskyddad PPE

Innehåll

HSE-krav Entreprenörer	1
1. STP HSE-policy	4
2. Arbetsmiljöarbete hos entreprenören	5
3. Arbetsmiljöansvar.....	5
4. Arbete i STP:s anläggningar	6
5. Arbetsmiljöplan	6
6. Säkerhetsutbildning.....	6
7. Olyckor och tillbud.....	7
8. Ordning och Reda	7
9. Elsäkerhet	7
10. Heta arbeten.....	8
11. Arbete på höjd.....	8
12. Stegar och ställningar	8
13. Arbete på tak	9
14. Slutna utrymmen.....	9
15. Ensamarbete.....	9
16. Användning av arbetsutrustning	9
17. Lyftanordningar och lyftredskap	10
18. Öppnande av hål	11
19. Personlig skyddsutrustning	12
20. Buller	12
21. Kemikaliesäkerhet	13
22. CO2- släcksystem.....	13
23. Explosionsklassade områden.....	13
24. Alkohol och Droger.....	13
25. Trafiksäkerhet.....	14
26. Efterlevnad av regler	14
27. Tillträde.....	14
28. Avfall.....	15
29. Rökning.....	15
HSE requirements Contractors.....	16
1. STP HSE policy.....	17
2. Work-environment and safety processes at contractors.....	18

- 3. Work environment responsibility..... 18
- 4. Work performed at STP’s facilities. 19
- 5. Safety and Health (work environment) plan 19
- 6. Safety training 19
- 7. Accidents and near accidents..... 20
- 8. Housekeeping..... 20
- 9. Electrical safety..... 21
- 10. Hot works 22
- 11. Work at height..... 22
- 12. Ladders and scaffolding..... 23
- 13. Roof work 24
- 14. Confined spaces..... 24
- 15. Working alone 24
- 16. Use of work equipment..... 24
- 17. Lifting devices and lifting accessories..... 25
- 18. Hole opening 26
- 19. Personal protective equipment..... 27
- 20. Noise..... 27
- 21. Chemical safety 27
- 22. CO2- fire extinguishing system..... 28
- 23. ATEX categorized areas 28
- 24. Alcohol and drugs..... 28
- 25. Traffic safety 29
- 26. Regulatory compliance..... 29
- 27. Access 29
- 28. Waste..... 30
- 29. Smoking 30

1. STP HSE-policy



Health, Safety and Environmental (HSE) Policy

Sydskraft Thermal Power ABs verksamhet ska utgå från omtanke om människa och miljö i det dagliga arbetet. Visionen kring detta kallar vi för Beyond Zero och den innehåller delar som ständigt lärande, att vi ska göra de bästa valen för både medarbetare, kunder, leverantörer och samhället. Men också att vi handlar ansvarsfullt för att minska vår påverkan på miljön och att vi hanterar våra anläggningar som vi behandlar våra medarbetare – det vill säga lär känna dem väl och bemöter dem med respekt.

Vår verksamhet har en nollvision när det gäller miljö-, arbetsmiljö- och säkerhetsincidenter.

Vår ambition är att:


- alla medarbetare, allmänheten, entreprenörer, leverantörer, myndigheter och övriga intressenter ska ömsesidigt uppskatta och ha förtroende för driften av vår verksamhet genom vårt handlingskraftiga och ansvarsfulla HSE-arbete.
- vårt HSE-arbete ska bidra till att stärka vår konkurrenskraft och styra mot utvecklingen av ett hållbart samhälle.

Detta når vi genom att:

- chefer och ledare visar ett tydligt och engagerat ledarskap samt involverar och samråder med medarbetarna och deras representanter
- varje medarbetare tar ansvar för HSE och har rätt att avbryta ett arbete som genomförs på ett osäkert sätt
- med stöd av ledningssystemet sätta ständiga förbättringsmål och följa upp verksamheten för att positivt påverka arbetsmiljön och den yttre miljön
- uppfylla och sträva mot att överträffa kraven i tillämpliga lagar, bestämmelser, riktlinjer och koncerngemensamma policies och regler
- arbeta för att upprätthålla branschledande anläggningsstatus och processsäkerhet
- som en naturlig del i det dagliga arbetet jobba kontinuerligt med att reducera riskerna och förbättra våra HSE-aspekter i verksamheten
- utforma den fysiska, psykiska och sociala arbetsmiljön så att den främjar goda arbetsresultat, trygghet och trivsel, samt förebygger olycksfall och ohälsa för alla som befinner sig på våra arbetsplatser
- skapa förutsättningar för en inkluderande och jämställd arbetsplats som strävar efter mångfald
- arbeta förebyggande för att skydda människa, miljö och egendom mot olyckor, bränder, skador och faror som negativt kan påverka vårt dagliga arbete med produktion och leverans av energi samt avveckling av verksamheter
- arbeta för att främja en miljömässig hållbarhet
- öppet redovisa vårt miljö- och arbetsmiljöarbete för allmänhet, myndigheter och andra intressenter
- bedriva öppen, saklig och snabb kommunikation intern och externt

Sydskraft Thermal Power ABs HSE-policy ska vara tillgänglig för alla som har tillträde till våra anläggningar samt på begäran.

Karlskhamn den 26 september 2022


Henrik Svensson, VD

2. Arbetsmiljöarbete hos entreprenören

Samtliga entreprenörer som utför arbete i våra anläggningar skall ha ett program för systematiskt arbetsmiljöarbete.

Detta innebär att man antingen är certifierad mot någon relevant standard eller har motsvarande processer i verksamheten.

Saknas certifiering kan STP revidera entreprenörens rutiner för att verifiera att ett systematiskt arbetsmiljöarbete föreligger.

Ovanstående krav gäller också entreprenörens underentreprenörer.

Varje entreprenör skall visa hur han/hon uppfyller sitt systematiska arbetsmiljöarbete. Antingen genom att redovisa auditering mot etablerad standard eller mot STP:s standard.

3. Arbetsmiljöansvar

Varje entreprenör ansvarar för Hälsa och Säkerhet för sin personal. Alla individer har ett eget ansvar att följa föreskrifter, instruktioner och rutiner som gäller på arbetsområdet.

Entreprenörer som verkar på STP:s arbetsplatser är skyldiga att samverka och delta i arbetet med att förebygga olycksfall och ohälsa på arbetsplatsen.

Allt arbete ska ske enligt Arbetsmiljöverkets gällande föreskrifter.

STP:s specifika krav

Varje entreprenör skall ha minst en namngiven person som samordnar arbetsmiljöarbetet på arbetsplatsen.

För varje arbete entreprenören utför skall det finnas en säkerhetsansvarig person. Denna tar emot och lämnar tillbaka arbetstillstånd samt svarar för att arbetsplatsen är säker.

Entreprenören uppmuntras till att genomföra dagliga arbetsmöten där metod och säkerhetsaspekter diskuteras. Likaså uppmuntras genomförande av säkerhetsronder med syftet att identifiera potentiella risker.

4. Arbete i STP:s anläggningar

Allt arbete på STP:s anläggningar kräver Arbetstillstånd.

Arbetstillstånd utfärdas av anläggningens driftorganisation efter anmodan av beställare. Framförhållning på ca 2 dagar krävs normalt för att slippa väntetid.

5. Arbetsmiljöplan

Det ska i varje entreprenad (gäller bygg och anläggningsarbete) upprättas en arbetsmiljöplan efter att avtal har ingåtts. Syftet med arbetsmiljöplanen är att definiera de metoder, verktyg, arbetsprocesser och risker som är kritiska för entreprenaden för att förebygga olyckor och ohälsa under entreprenaden. Arbetsmiljöplanen kan vara generell eller specifik men ska vid behov anpassas till den enskilda entreprenaden. Arbetsmiljöplanen ska även ge förutsättningar för styrning och uppföljning.

Beställaren bedömer omfattning av arbetsmiljöplanen. Arbetsmiljöplanen ska minst beskriva:

- Arbetsmiljöorganisation och struktur
- Vid bygg- och anläggningsarbeten ange vem som är byggarbetsmiljösamordnare (BAS-P, BAS-U)
- Hur olyckor och tillbud dokumenteras och rapporteras till beställaren
- Nödlägesrutinrutin med larmlista och kontaktpersoner
- Kemikalieförteckning och hantering av kemikalier
- Riskbedömning och nödlägesanalys och vad gör man för att minimera riskerna
- De regler som ska tillämpas på byggarbetsplatsen
- En beskrivning av de särskilda åtgärder som ska vidtas för att arbetet ska kunna bedrivas säkert och uppfylla lagkraven

6. Säkerhetsutbildning

STP:s specifika krav

För att utföra arbete på anläggningarna krävs att samtliga entreprenörer genomgått SSG Entre samt STP Lokala säkerhetsutbildning.

Det åligger entreprenören att själv anmäla sig och genomföra SSG utbildningarna i förväg.

I samband med att nycklar och/eller passerkort kvitteras ut, ges en kortare information om återsamlingsplats, olika typer av larm mm.

Den lokala SSG utbildningen har en giltighet på 12 månader och SSG Entré på 36 månader.

7. Olyckor och tillbud

Entreprenör ansvarar för rapportering till myndigheter (Arbetsmiljöverket, Elsäkerhetsverket etc.) vid allvarliga olycksfall eller tillbud.

STP:s specifika krav

Olyckor och tillbud ska alltid omgående rapporteras till beställaren. Rapporteringen sker via av beställaren anvisat system.

Entreprenören ansvarar för utredning av olycksfall och tillbud. Utredningarna ska lämnas till beställaren. STP har rätt att delta i utredning, alternativt tillsätta en egen utredning. Entreprenören är även skyldig att delta i eventuell utredning som genomförs av STP.

Entreprenören skall – även avseende egna underentreprenörer –utan dröjsmål redovisa antalet olycksfall som lett till sjukskrivning mer än en dag, hur många frånvarodagar (kalenderdagar) varje olycksfall lett till samt det totala antalet arbetade timmar.

Entreprenörens personal ska ha HLR-utbildning som är högst 3 år gammal.

8. Ordning och Reda

STP:s specifika krav

Ordning och reda på arbetsplatsen minimerar risker för olyckor. Entreprenör ska upprätthålla ordning och reda på entreprenadområdet och i personalutrymmen.

På arbetsplatsen skall dagligen städas. En gång i veckan görs en genomgripande städning

9. Elsäkerhet

Myndighetskrav

För samtlig elektrisk utrustning och dess handhavande på arbetsplatsen gäller Elsäkerhetslagen 2016:732 för elektriska starkströmsanläggningar. Även de som vid arbete tillämpar säkerhetsåtgärder som följer någon annan standard eller praxis än svensk standard ska doku

Ett elinstallationsföretag ska:

1. utöva egenkontroll över arbetet enligt ett egenkontrollprogram som säkerställer att elinstallationsarbete utförs enligt de krav som ställs.
2. se till att elinstallationsarbete endast utförs av en elinstallatör eller av någon som omfattas av företagets egenkontrollprogram enligt 1.

10. Heta arbeten

Tillfälliga brandfarliga Heta Arbeten får inte utföras utan tillstånd från ansvarig person samt att åtgärder som skapar förutsättningar för betryggande brandsäkerhet uppfylls. Vid brandfarliga Heta Arbeten ska Försäkringsbolagens och Brandskyddsföreningens säkerhetsregler följas.

STP:s specifika krav

Vid Heta Arbeten, t.ex. svetsning, skärning, slipning, lödning, varmluftsbearbetning, krävs ett skriftligt tillstånd, giltigt certifikat för både utförare och brandvakt och efterlevnad av STP:s rutiner. STP:s rutiner tillgodoser de säkerhetsregler för heta arbeten som föreskrivs av Försäkringsbolagen och Svenska Brandskyddsföreningen.

Observera att det förekommer AT(EX) klassade områden (dvs. risk för explosiv atmosfär), där det råder förbud mot Heta Arbeten. Vid bebov av brandfarliga heta arbeten i förbudszoner måste tillstånd inhämtas från föreståndaren.

11. Arbete på höjd

Arbete på höjd innebär särskilda risker och ska alltid hanteras i arbetstillståndet och i arbetsmiljöplanen.

Arbeten på olika höjdnivåer i samma område får enbart i undantagsfall förekomma samtidigt. Om sådana arbeten ändå inte kan undvikas, så måste samordning ske mellan berörda arbetslag. Samordningen ska omfatta riskbedömning och nödvändiga åtgärder för riskeliminering samt ansvarsfrågor.

Om fallskyddsutrustningen skall användas skall användaren vara väl förtrogen med hur man tar på denna, vilka fästpunkter som skall användas och hur man agerar vid ett eventuellt fall och blir hängande i fallskyddet. Denna kunskap skall fås genom lämplig utbildning/information om fallskyddsanvändning.

Vid arbete som STP AB bedömer som klättring i mast, stolpe, skorsten eller liknande, där nivåskillnaden är mer än 13 meter, ska utföraren ha Tjänstbarhetsintyg. Vid sådant arbete måste även en separat riskanalys göras tillsammans med ett Arbetstillstånd.

12. Stegar och ställningar

Arbete från stege får endast förekomma om riskerna med att använda stege är så små att annan säkrare utrustning inte är befogad. Ställningar skall besiktigas varje vecka och kontrolleras dagligen eller vid förändring.

STP:s specifika krav

Högsta tillåtna arbetshöjd från stege är två meter.

Medtagna stegar skall vara typgodkända samt godkända av STP kontaktperson före användning.

Alla ställningar byggs av STP anvisad ställningsbyggare.

Innan ställning börjar byggas ska särskild riskbedömning genomföras av ställningsbyggande entreprenör och ansvarig för entreprenaden.

Vid riskbedömningen ska också bedömas behov av avspärning runt ställningen under uppförandet och bruksskedet. Se rutin för arbetstillståndshantering hur ställningar hanteras på de olika anläggningarna.

Ställning får inte beträdas förrän den har godkänts av ansvarig ställningsbyggare, användaren samt av STP:s representant.

Ställningar skall kontrolleras dagligen och skriftligt besiktigas varje vecka.

Alla ändringar av ställning görs av ställningsbyggare

13. Arbete på tak

STP:s specifika krav

Vid arbete på tak, närmare än två meter från kanten, skall begränsande fallskyddsutrustning användas. Kan inte ovanstående användas skall fallskyddsutrustning (livsele) användas.

14. Slutna utrymmen

STP:s specifika krav

Särskilt tillstånd och rutiner gäller för denna typ av arbete.

Innan arbete påbörjas skall gasfrihetsförklaring och syremätning genomföras.

Yttre säkerhetsperson som för accesslista på personer i utrymmen skall finnas.

Utrymningssslinga och ficklampa skall finnas tillgänglig.

15. Ensamarbete

Allt ensamarbete måste godkännas av STP samt att den gällande rutinen för ensamarbete måste följas.

16. Användning av arbetsutrustning

Myndighetskrav

Med arbetsutrustning avses maskin, anordning, verktyg, redskap eller installation som används i arbetet.

Undersökning och riskbedömning ska göras för att bedöma om den arbetsutrustning som väljs och används är lämplig för det arbete som ska utföras så att den kan användas med betryggande säkerhet.

Arbetsutrustning får bara användas för det ändamål och under de förutsättningar den är avsedd och lämpad för.

STP:s specifika krav

För att få använda truckar, lyftverktyg, traverser etc. krävs att:

- Giltigt utbildningscertifikat uppvisats och registrerats.
- Skriftligt tillstånd från egen arbetsgivare samt STP erhållits

Användandet av el-, maskin- eller handverktyg ska beaktas i riskanalys inför arbetet.

Vinkelslipar skall vara försedda med handtag så att de kan hållas med två händer samt vara utrustade med rondell/skivskydd, broms, kastskydd och "dödmansgrepp".

Nödvändiga säkerhetsåtgärder och personlig skyddsutrustning ska tillgodoses under arbetet.

Observera att kniv med öppet blad INTE får användas. Vid behov att använda kniv måste riskanalys göras och tillstånd inhämtas från respektive anläggningsansvarig.

17. Lyftanordningar och lyftredskap

Riskbedömning

Riskbedömning ska genomföras innan lyftanordning och eller lyftredskap används. Riskbedömningen ska dokumenteras.

Planering

Lyftarbete ska planeras och organiseras så att inga farliga situationer uppstår.

Kompetens

Entreprenören ska ha skriftlig dokumentation på praktisk erfarenhet och teoretisk kunskap för dem som ska arbeta med lyftanordningar och lyftredskap.

Dokumentation ska kunna visas upp på anmodan från beställaren.

Besiktning underhåll

Lyftanordning och lyftredskap ska underhållas och genomgå fortlöpande tillsyn och dagliga kontroller. Journal ska föras över underhåll och fortlöpande tillsyn. Journal och besiktningsintyg ska kunna visas upp på anmodan från beställaren.

STP:s specifika krav

Lyftredskap

Alla lyftredskap (lyft ok, stroppar etc.) som tas in på området skall vara godkända och märkta enligt de regler som svenska myndigheter kräver.

All personal som utför lyft ska ha tillräcklig utbildning för ändamålet, t.ex. traversförarutbildning, säkra lyft eller liknande. De skall dessutom vara godkända och registrerade av STP.

18. Öppnande av håll

STP:s specifika krav

Bedömning av behov av avspärrning

Före håltagning samt borttagande av lock, lucka, greting eller liknande, ska behovet av avspärrning bedömas. Vid bedömningen ska hänsyn tas till tredje man, medarbetare på anläggningen och medarbetare i den egna arbetsgruppen. Vid behov av avspärrning ska införskaffning av utrustning härför ske före håltagning. Öppningar i mark eller golv ska alltid spärras av.

Behov av vakt

Om tillräcklig avspärning inte kan genomföras på nöjaktigt sätt, så ska vakt placeras vid hålet. Personen som vaktar får inte samtidigt ha några andra arbetsuppgifter.

Det är alltid den som öppnat upp ett hål som ansvarar för att nödvändig avspärning sker.

19. Personlig skyddsutrustning

Personlig skyddsutrustning ska väljas utifrån på arbetsplatsen aktuella risker, arbetsmoment samt vara individuellt utprovade. För skyddsmask gäller sedan 1/1 2025 även att all personal som ämnar använda skyddsmask först måste genomgå ett anpassningsprov, för att få lov att använda sådan.

Personer som ej genomfört test kan dock använda en s.k. fläktassisterad mask.

Entreprenören tillhandahåller sin personal personlig skyddsutrustning samt skyddskläder och ansvarar för att personal använder den personliga skyddsutrustning som föreskrivs.

STP:s specifika krav

Personlig skyddsutrustning skall väljas utifrån risker på arbetsplatsen. Omfattningen regleras i arbetstillståndet eller är skyltade vid särskilda riskområden.

Vid arbeten inom PPE-zon gäller dock nedanstående minimumstandard:

Typ	Motsvara standard	Obligatoriskt	Medföras
Skyddshjälm	EN 397	X	
Skyddsglasögon	EN 166 Klass S	X	
Skyddsklädsel heltäckande	Varsel – EN 471 Class 2 Flamskydd – EN ISO 11612	X	
Skyddsskor	EN ISO 20345 Class S3	X	
Hörselskydd	EN 352		X
Skyddshandskar	EN 388 2121		X

20. Buller

Buller förekommer i STP AB:s verksamheter och detta måste alltid beaktas i planering och riskbedömning.

STP:s specifika krav

Entreprenören ska informera beställaren innan buller eller vibrationsstörande arbeten påbörjas.

21. Kemikaliesäkerhet

Före arbete med kemiska produkter ska riskbedömning ske. Bedömningen ska ligga till grund för val av bl.a. arbetsmetod, riskreducerande åtgärder och personlig skyddsutrustning. Riskbedömning och val av skyddsåtgärder ska dokumenteras.

STP:s specifika krav

Alla kemikalier entreprenören avser använda på STP:s anläggningar skall föränmälas genom överlämnande av säkerhetsdatablad och riskanalys avseende användandet. Först efter godkännande av STP och uppläggning i STP:s kemidatabas får kemikalierna användas.

Temporär förvaring sker på av STP anvisad plats eller för ändamålet uppställda kemikalieskåp. Alla kemikalier förvaras i märkta kärl.

Gasflaskor ska förvaras på anvisad plats över natten.

Entreprenören ansvarar för att medtagna kemikalier avlägsnas från arbetsplatsen när arbetet är avslutat.

22. CO₂- släcksystem

STP:s specifika krav

Vissa utrymmen på anläggningarna är skyddade med CO₂ (koldioxid) släcksystem.

För att vistas inom dessa områden krävs blockering av släcksystemet, gasfrihetsförklaring och ett giltigt arbetsbevis.

Specifika regler gäller för olika arbetsplatser.

23. Explosionsklassade områden

STP:s specifika krav

Vissa utrymmen på anläggningarna är explosionsklassade (ATEX).

Anledningen är att det kan finnas olja, naturgas, vätgas eller annan brandfarlig vara.

För varje utrymme gäller specifika säkerhetsregler. Föreståndaren för brandfarliga och explosiva varor måste informeras före arbete påbörjas i de aktuella utrymmena.

24. Alkohol och Droger

STP:s specifika krav

Allt arbete under inverkan av alkohol eller droger är förbjudet, liksom att medföra alkohol eller droger till arbetsstället.

Slumpvisa alkohol och drogtestar genomförs utan förvarning och på initiativ av STP.

25. Trafiksäkerhet

Vid arbete på, intill eller under väg gäller särskilda krav på avspärningar och varselkläder.

STP:s specifika krav

Entreprenören åtar sig att följa gällande trafikregler och arbetsområdets trafikplan.

Parkering inom området skall ske på anvisad plats.

De trafikregler som gäller på anläggningen ska följas.

Fotgängare har företräde.

Telefonsamtal bör undvikas vid förflyttning med fordon eller till fots, eftersom uppmärksamheten på omgivningen försämras.

26. Efterlevnad av regler

STP:s specifika krav

STP har höga ambitioner inom miljö- och arbetsmiljöarbetet både för egna anställda och för de entreprenörer vi anlitar. För att säkerställa att överenskomna regler och rutiner följs förbehåller sig STP rätten att genomföra kontroller för att följa upp miljö- och arbetsmiljöarbetet. Kontroller kan genomföras såväl föranmälda som oanmälda. Entreprenör ska medverka vid dessa kontroller.

Personer som medvetet bryter mot STP:s regler riskerar att få ett gult kort (Varning).

Vid upprepade förseelser eller vid grovt åsidosättande av STP Värmekrafts regler kommer rött kort att delas ut. Detta innebär att personen ej är önskvärd på anläggningen.

Efter avslutat projekt skall entreprenören tillsammans med leverantören utvärdera verksamheten och identifiera förbättringsområden.

27. Tillträde

STP:s specifika krav

Alla som skall utföra arbete på anläggningarna skall först gå säkerhetsutbildning (se pkt. 5)

Efter utbildningen fås passerkort med den behörighet kontaktpersonen anger.

Säkerhetsutbildningen sker enligt regler på respektive anläggning.

Besökare anmäler sig i receptionen eller till sin kontaktperson. Besökskort utfärdas enligt rutin på respektive anläggning. Besökskortet ska bäras synligt.

Besöksmottagaren ansvarar för besökaren och skall alltid ledsaga besökaren.

28. Avfall

STP:s specifika krav

Avfall ska sorteras och läggas på anvisad plats.

Farligt avfall skall hanteras på av beställaren anvisat sätt.

Golvbrunnar och avlopp är normalt anslutna till utrustning för detektering och larm för olja. Utsläpp av vätska eller annat material genom golvbrunn eller avlopp är inte tillåtet utan tillstånd från STP.

29. Rökning

STP:s specifika krav

Generellt rökförbud råder på samtliga av STP:s anläggningar. Rökning utomhus är endast tillåtet på anvisad plats enligt lokala regler. (gäller även e-cigarretter)

<i>Typ av Dokument</i> Dokument	<i>Sida</i> 16 (30)
<i>Datum</i> 2026-01-14	<i>Dokument-ID</i> DOCID-1165896853-423
<i>Sekretessklass</i> Publik	<i>Version</i> 18.0
<i>Dokumentägare</i> Pålbro, Jonas	<i>Företag</i> Sydkraft Thermal Power AB
<i>Titel</i> STP - HSE-krav entreprenörer	<i>Godkänd av</i> Thunell, Anna

HSE requirements Contractors

STP's overriding objective is that no individual should be the victim of a serious accident or suffer from any work-related illness.

This objective applies to STP's own employees and to those contractors working for STP.

Achieving this objective requires the collaboration of every individual, both STP's own employees and all contractors, to work towards a safe work environment.

All the following requirements applicable to contractors and suppliers must be included in the price agreed between the parties.

Date	Revision
-------------	-----------------

<i>2019-11-08</i>	<i>Minor adjustments</i>
-------------------	--------------------------

<i>2021-09-16</i>	<i>Minor adjustments</i>
-------------------	--------------------------

<i>2022-03-08</i>	<i>Minor adjustments</i>
-------------------	--------------------------

<i>2022-07-11</i>	<i>Updated regarding open blade knife</i>
-------------------	---

<i>2024-03-15</i>	<i>Clarification and minor changes in chapter 11. Work at heights.</i>
-------------------	--

<i>2024-06-26</i>	<i>Update of EN standard for flame retardant PPE</i>
-------------------	--

1. STP HSE policy



Health, Safety and Environmental (HSE) Policy

English translation for information purpose only. The Swedish version of the policy is binding.

Sydskraft Thermal Power AB's business should be based on concern for people and the environment in our daily work of producing and supplying energy. We call the vision around this Beyond Zero and it contains elements such as continuous learning, that we must make the best choices for both employees, customers, suppliers and society. But also that we act responsibly to reduce our impact on the environment and that we manage our facilities as we treat our employees - that is, get to know them well and treat them with respect.

Our business has zero vision when it comes to environmental, work environment and safety incidents.

Our aim is that:

- all employees, the general public, contractors, suppliers, public authorities and other stakeholders should feel mutual appreciation for and faith in the way we run our business through our proactive and responsible HSE work.
- our HSE work should help to strengthen our competitive ability and guide us towards a sustainable society.

We will achieve this by:

- managers and supervisors demonstrating clear and committed leadership and involve and consult with employees and their representatives
- all employees take responsibility for HSE and have the right to stop work that is carried out in an unsafe manner
- setting continuous improvement goals and following up the business with the support of the management system to ensure a positive effect on the working environment and the external environment
- complying with and preferably exceeding the requirements of applicable laws, provisions, guidelines, policies and rules
- working to maintain industry-leading plant status and process safety
- as a natural part in the day-to-day work continuously reduce risks and improve our HSE aspects of operations
- designing the physical, mental and social working environment to ensure that it promotes good work results and well-being, and prevents accidents and ill-health for everyone in our workplaces
- working preventively to protect people, the environment and property from accidents, fires, harm and dangers that could negatively affect our day-to-day work of producing and supplying energy and decommissioning of operations
- create the conditions for an inclusive and equal workplace that strives for diversity
- working to promote environmental sustainability
- carry out factual and quick communication both internally and externally
- transparently reporting our health, safety and environmental work to the general public, public authorities and other stakeholders

Sydskraft Thermal Power AB's HSE Policy will be accessible to everyone with access to our plants and on request.

Karlshamn September 26, 2022

A handwritten signature in black ink, appearing to read 'Henrik Svensson'.

Henrik Svensson, CEO

2. Work-environment and safety processes at contractors

All contractors engaged in work at our facilities must have a program for systematic work-environment and safety process in place.

This entails that the contractor must either be certified according to a relevant standard or have the equivalent processes in its operations.

Should certification be lacking, STP can review the contractor's procedures to verify that a systematic work- environment and safety process exists.

The above requirements also apply to any subcontractors to the contractor.

Each contractor is to demonstrate how the systematic work-environment and safety process is complied with, either through reporting the results of auditing against an established standard or against STP's standard.

3. Work environment responsibility

Each contractor is responsible for the Health and Safety of its employees. Everyone has a responsibility to comply with applicable regulations, instructions and procedures at the workplace.

Contractors operating at STP's workplaces are obliged to collaborate and participate in initiatives aimed at preventing accidents and ill health at the workplace.

All work must be performed in compliance with the applicable regulations of the Swedish Work Environment Authority provision.

STP's specific requirements

Each contractor must have at least one named person designated as responsible for the coordination of work-environment and safety efforts at the workplace.

For each job performed by the contractor there must be a person who is responsible for safety. This person shall accept and return the work permit and is responsible for the safety at the workplace.

Contractors are encouraged to perform "toolbox meetings" to discuss the work method and safety issues. Safety walks, with the purpose to identify potential hazards, are also encouraged.

4. Work performed at STP's facilities.

All work performed at STP's facilities requires a work permit.

Work permits are issued by the operating management of the facility. No work can commence without the appropriate permits being in place. The lead time is normally two days, which means that advance planning is required to avoid delay.

5. Safety and Health (work environment) plan

Regulatory requirements

Each construction contract requires the production of a safety and health plan after entering a contract. The aim of the safety and health plan is to define the contract-critical methods, tools, work processes and risks to prevent accidents and ill health during the performance of the contract. The safety and health plan may be general or specific but must when needed be adapted to the specific contract. The safety and health plan must also provide the prerequisites for control and follow-up.

The purchaser will review the content and scope of the safety and health plan supplied by the contractor. At a minimum, the safety and health plan must:

- Describe the safety and health organization and structure.
- Regarding building and civil engineering work, specify the individual responsible for coordination of safety and health aspects (BAS-P, BAS-U, construction safety coordinator)
- Describe how accidents and near accidents are documented and reported to the purchaser.
- Contain emergency procedures, including an alarm list and contact people
- Include a list of chemicals and a description of how to handle the chemicals
- Contain a risk assessment and an emergency analysis as well as instructions to minimize risks.
- Describe the applicable rules for the construction site.
- Include a description of the actions to be taken to ensure safe performance of work and compliance with legal requirements.

6. Safety training

STP's specific requirements

All contractors must complete both SSG Entré and STP AB:s SSG local education. It's up to the contractor to register and perform both SSG trainings in advance.

A local training/exhibition will take place when keys and/or entrance cards are handed out. The local SSG training is valid for 12 months and the SSG Entré for 36 months.

7. Accidents and near accidents

The contractor is responsible for reporting to government agencies (the Swedish Work Environment Authority, the Swedish National Electrical Safety Board, etc.) in case of serious accidents or near accidents.

STP's specific requirements

Accidents and near accidents are always to be immediately reported to the purchaser. Reports are made via the appropriate system as shown by the purchaser. The contractor is responsible for investigating any accidents and near accidents and the results of any such investigation are submitted to the purchaser. STP has the right to participate in any investigation or alternatively appoint its own investigation.

The contractor is also obliged to participate in any investigation appointed by STP.

Each month, the contractor must, on its own and its subcontractor's behalf, on completion of a contract or as agreed with the purchaser, report the number of accidents that have led to reporting sick for a period in excess of one day, the number of days of absence (calendar days) each accident led to, and the total number of hours worked.

All personnel must have undergone cardiopulmonary resuscitation (CPR) training within the past three years.

8. Housekeeping

STP's specific requirements

A clean and organized workplace minimizes the risk of accidents. Contractors must maintain a clean and organized workplace in the area where the contract work is being performed and in areas reserved for use by employees.

The workplace is to be cleaned daily and be thoroughly cleaned once a week.

9. Electrical safety

For all electrical equipment and its handling in the workplace, the Electrical Safety Act 2016:732 for electrical high-voltage installations applies. Even those who, in their work, apply safety measures that follow a standard or practice other than the Swedish standard must document their risk assessment and issue instructions

An electrical installation company shall:

1. Exercise self-control over the work according to a self-control program that ensures that electrical installation work is carried out according to the required standards.
2. Ensure that electrical installation work is only performed by an electrician or by someone covered by the company's self-control program according to point 1

STP's specific requirements and established industry practices/standards, Electrical Safety Instructions (ESA)

Or similar types like ELSA or EVA. However, these instructions are mostly applicable for work with low voltage: a maximum of 1000 V AC or a maximum of 1500 V DC.

10. Hot works

Regulatory requirements

Hot works entailing a temporary fire hazard may not be performed without a permit from the person responsible and measures being in place that create the necessary conditions for safety from a fire-safety perspective. The Swedish insurance companies and Brandskyddsföreningen (SBF) have developed safety rules that apply for hazardous hot works.

STP's specific requirements

All hot works, e.g., welding, grinding, burning, heating, and cutting, requires a written permit, valid education for both performing personnel and fire watch and compliance with STP's procedures for hot works. STP's safety rules comply with the requirements from the Swedish insurance companies and Brandskyddsföreningen (SBF).

Note that there are ATEX ("Atmosphères Explosible") areas within STP's facilities. Hot works are prohibited in such areas, due to the risk of potentially explosive atmosphere.

If there is a need for hot work in prohibited zones, the Flammable and explosive goods manager, always must be informed.

11. Work at height

Regulatory requirements

Work at height entails risks and must always be addressed in the work-environment (WCM) and safety plan.

Simultaneous work on varying height levels in the same area may only occur in exceptional cases. If such work is unavoidable, the work teams involved must be coordinated. This coordination must include a risk assessment and the requisite actions must be taken to eliminate risk and to deal with responsibility issues.

When climbing a mast, post, chimney or similar, where the level difference is more than 13 meters, the performer must have Serviceability certificate.

For such work, a separate risk analysis must also be carried out together with a Work Permit

If the fall-protection equipment is to be used, the user should be familiar with how to use it, which attachment points are to be used and how to act in a potential fall and get caught in the fall protection equipment. This knowledge should be obtained through appropriate training / information on how to use the equipment.

12. Ladders and scaffolding

Work may only be performed from a ladder if the associated risks are so small that other safety equipment is not justified.

Included ladders must be type-approved and approved by STP before use.

Scaffolding must be inspected on a weekly basis and checked each day or when modifications are made.

STP's specific requirements

The highest permitted working height from a ladder is two meters.

All scaffolding is to be assembled by scaffolding contractors appointed by STP.

Prior to assembly of scaffolding, a separate risk assessment is to be performed by the scaffolding contractor and the individual responsible for the construction contract. The risk assessment includes an assessment of the need for cordoning off an area around the scaffolding during its assembly and when in use. For details regarding proper management of scaffolding at the various facilities, refer to the procedure for the management of certificates of work completed.

Scaffolding may not be used until it has been approved by scaffolding contractor responsible for its assembly, the user and by STP's representative.

Scaffolding must be checked daily, and a written inspection performed each week.

All modifications to scaffolding must be performed by a scaffolding contractor.

13. Roof work

STP's specific requirements

Fall-prevention equipment must be used for roof work performed within two meters of the edge of the roof. Where the above is not possible, a safety harness must be used.

14. Confined spaces

STP's specific requirements

Separate permits and procedures apply for this type of work.

Prior to starting work, the space must be declared free from hazardous gas and oxygen levels must be measured. An external safety person must be in place and maintain an access list of the individuals in the space. An evacuation safety line and flashlights must be available.

15. Working alone

All solo work must be approved by STP and that the current routine for solo work must be followed.

16. Use of work equipment

Work equipment is defined as machinery, appliances, tools, instruments or installations used in the work.

Inspections and risk assessment must be performed to assess whether the work equipment selected and used is appropriate for the work being performed so that it can be used in a safe manner.

Work equipment may only be used for the purpose and under the conditions for which it is intended and appropriate for.

STP's specific requirements

The following requirements apply for the use of forklifts, lifting equipment, overhead travelling cranes etc.:

- Presentation and registration of a valid training certificate.
- Written permit from STP.

The usage of electrical, mechanical or hand tools shall be paid particular attention in the pre-job planning and risk assessment.

Grinders shall be equipped with handles so they can be held with two hands and be equipped with pad / disc protection, brake, kick-back guard and "dead man's handle".

Necessary precautions shall be met, and applicable personal protection equipment shall be used, during the work.

Note that knife with open blade must not be used. If it is necessary to use a knife, a risk analysis must be performed, and a permit obtained by the site manager.

17. Lifting devices and lifting accessories

Risk assessment

A risk assessment must be performed and documented prior to use of lifting devices and lifting accessories.

Planning

Lifting operations must be planned and organized to avoid the occurrence of hazardous situations.

Qualification

The contractor must have written documentation of practical experience and theoretical knowledge of any individuals working with lifting devices and lifting accessories. The documentation must be available when requested by the purchaser.

Inspection and maintenance

Lifting devices and lifting accessories must be maintained and subject to continuous inspection and daily controls. A journal must be kept of maintenance and ongoing inspections. The journal and inspection certificates must be available when requested by the purchaser.

STP's specific requirements

Lifting accessories

All lifting accessories (lifting yokes, straps etc.) that are brought into the area must be approved and labeled in line with the regulations stipulated by Swedish government agencies.

All personnel performing lifting operations must possess sufficient training for that purpose, meaning overhead crane operator training, safe lifting or similar. These training programs must also be approved and registered by STP.

18. Hole opening

STP's specific requirements

Assessment of the need for barriers

Any need for barriers must be assessed prior to hole opening and the removal of covers, hatches or similar. The assessment must take into consideration third parties, colleagues at the facility and colleagues within the actual work team. Where barriers are required, the necessary equipment must be procured prior to hole opening. Openings in the ground or floor shall always be barriered off.

Guard requirement

If adequate barriers are not possible in a reasonable manner, a guard must be placed by the hole. This person is not permitted to have any other work duties.

The individual that opens a hole is the person responsible for ensuring that it is adequately barriered off.

19. Personal protective equipment

Regulatory requirements

Personal protective equipment (PPE) must be selected appropriately given the actual risks and tasks for the workplace.

The contractor is to provide PPE for its employees and is responsible for ensuring that his employees use the prescribed PPE.

For protective masks, since January 1, 2025, all personnel who intend to use a protective mask must first undergo a fit test before being allowed to use one. However, people who have not completed the test can use a so-called fan-assisted mask.

STP's specific requirements

PPE must be selected appropriately given the actual risks at the workplace. The scope is set out in the work permit or is detailed through signs at specific risk areas.

The following minimum requirements always apply for work in PPE zones:

Type	Corresponding standard	Mandatory	Carried
Hard hat	EN 397	X	
Protective goggles	EN 166 Class S	X	
Protective clothing fully covering	High-visibility – EN 471 Class 2 Flame retardant – EN ISO 11612	X	
Safety shoes	EN ISO 20345 Class S3	X	
Hearing protection	EN 352		X
Protective gloves	EN 388 2121		X

20. Noise

STP's specific requirements

Noise occurs in STP's operations and this must always be taken into account in planning and risk assessment.

The contractor must inform the client before noise and vibration-disturbing work begins.

21. Chemical safety

A risk assessment must be performed prior to any work involving chemical products. The assessment is to form the basis for selecting items including the method of work,

risk-reducing measures, and PPE. The risk assessment and selection of protective measures must be documented.

STP's specific requirements

All chemicals that the contractor intends to use at STP's facilities must be applied for in advance through the submission of a safety data sheet and risk analysis for the use intended. Following approval by STP and entry into STP's chemical database, use of the chemicals is permitted.

No chemicals may be left outside or around the facility overnight or after completion of the work. All chemicals are to be stored in labeled containers.

Gas bottles must be stored at the designated location overnight.

The contractor is responsible for the removal of chemicals from the working place when the work is finished.

22. CO₂- fire extinguishing system

STP's specific requirements

Certain spaces at the facility may be protected by CO₂ (carbon dioxide) extinguishing system.

Entry to these areas requires the disabling of the extinguishing system, a declaration that the space is gas-free and a valid work permit.

Specific regulations apply to various workplaces.

23. ATEX categorized areas.

STP's specific requirements

Certain spaces at the facility may have been given an ATEX category due to the possible presence of oils, natural gas, hydrogen gas or other flammable substances.

Specific safety rules apply for such spaces. The manager of flammable and explosive goods must always be informed before starting work in an ATEX area.

24. Alcohol and drugs

STP's specific requirements

All work under the influence of alcohol or drugs is forbidden, as is the presence of alcohol or drugs at the workplace. A smoking ban applies at all STP's premises.

Unnotified, random alcohol and drug testing is performed on the initiative of STP.

25. Traffic safety

Separate requirements for safety barriers and high-visibility clothing apply for work on, adjacent to or under roads.

STP's specific requirements

The contractor undertakes to comply with the applicable traffic rules and the traffic plan for the workplace.

Parking in the area is only permissible in designated locations.

The local traffic regulations at the plant must be followed.

Pedestrians have right of way.

Telephone calls should be avoided when moving by vehicle or on foot, due to impaired attention on the surroundings.

26. Regulatory compliance

STP's specific requirements

STP has high ambitions for environmental and safety initiatives, both for its own employees and for those of the contractors that we use. In an effort to ensure compliance with the agreed rules and regulations, STP maintains the right to perform inspections to follow-up environmental and safety initiatives. Such inspections may be performed with or without any warning. Contractors are expected to participate in these inspections.

Any individual that consciously breaches STP's rules and regulations risks will receive a yellow card (written warning).

Repeated offences or serious breaches of STP's rules and regulations will result in the individual receiving a red card. This means that the individual is no longer welcome at the facility.

Following conclusion of the project, the contractor must evaluate operations and identify areas for improvement together with the supplier.

27. Access

STP's specific requirements

Any individual who is to perform work at the facilities must first undergo safety training (see section 6).

Following training, the individual will receive an access card, with access to areas specified by the authorized contact person.

Safety training is to be conducted pursuant to the rules of the applicable facility.

Visitors are to register at the reception. Visitors' passes are issued pursuant to the applicable procedures of the respective facility. The visitor pass must be worn visible.

The person receiving the visitor is responsible for the visitor and must always accompany the visitor.

28. Waste

STP's specific requirements

Waste is sorted and placed at the designated location. Hazardous waste is dealt with as instructed by the purchaser.

Floor drains and sewers are normally connected to equipment able to detect the presence of oil and give an alarm. No discharge of fluids or other material is allowed through the station drains without the permission of STP representative.

29. Smoking

STP's specific requirements

Smoking is only permitted in the designated areas. (also e-cigarettes)